

SPECIFICATION FOR DRIZIT® OIL ECONOMY 25 SPILL KIT



	0170/BOX/25
Container Size	54 x 42 x 15.5 cm
Container Volume	30 litres
Container Colour	Brown
Pack Wt (gross)	3.3 kg
Sorbency	26 - 33 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Container:	Cardboard box with dispensing slot and reinforced carry slots
Contents:	 25 Oil Pads 2 Oil Socks 125 x 7.5 cm 1 Dammit[®] X Ready Mix Slab 1 Pair of Gloves 1 Disposal bag and tie
Instructions for use:	It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn. Depending on the nature of the spill a combination of the contents of the kit may be used.
Compatibility:	The absorbents within this kit may be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils. Water-repellency exceeds requirements of BS 7959-2:2000. Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
Disposal:	Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
Safety Data:	Further technical advice is available if required.
Note:	All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018



