

SPECIFICATION FOR DRIZIT® OIL MINI KIT 2



	0170/MINI/2
Container Size	50 x 14 x 50 cm
Container Volume	n/a
Container Colour	Clear
Pack Wt (gross)	3.0 kg
Sorbency	26 - 32 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Container: Clear plastic snap handle bag

Contents:

- 20 Oil Pads
- 3 Oil Socks 125 x 7.5 cm
- 1 Dammit® X Ready Mix Slab
- 1 Pair of Gloves
- 1 Disposal bag and tie

Instructions for use: It is important that a suitable and sufficient Risk Assessment is carried out on each incident and correct PPE is worn.
Depending on the nature of the spill a combination of the contents of the kit may be used.

Compatibility: The absorbents within this kit may be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils.
Water-repellency exceeds requirements of BS 7959-2:2000.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 06/11/2018